

T&O / STOOL

Similar to the T Chair of the same series, the O Stool features a seat three-dimensionally cut out of wood, and the Mid and High models are equipped with a colored footrest. The oval hole in the center of the seat is provided for easily carrying the stool. The colored steel footrest and seat shape provide the same familiarity and freshness of the T Chair. It was named an O Chair because it looks like the shape of an "O" when viewed from above.



DESIGN



Photo by Nacasa & Partners Inc.

JASPER MORRISON , 2016 -

" O Stool is similarly of 3d machined solid wood and the stool mid and high have painted steel tube footrests. The handle, consisting of an elongated hole machined through the centre of the seat is shaped for maximum comfort when carrying the stool. It is also a familiar typology revitalised with improved comfort and new materials. "

MATERIAL & FINISH

maple




C-0
clear



NK-1*
natural black

ash




C-0
clear




NK-1*
natural black


oak



C-0
clear




NL-0
whitish



NK-1*
natural black

steel



black



green



red



silver

*black or silver are the only selectable steel colors for NK-1.

WARRANTY

We will guarantee the product for two years from the date of delivery of the product. For the content of quality assurance please see the "Warranty Policy" included in the product.

TESTS

ISO7173-L4 / Determination of strength and durability

ISO7174 / Determination of stability

TECHNICAL INFORMATION

WOOD

The wood used in this product is obtained from maple, ash or oak trees in North America that are managed and felled in a planned manner. If required, we can manufacture furniture with the FSC® or PEFC™ certification. In that case, however, a longer lead-time will be required to procure the wood.

METAL

The footrest is made from stainless steel tubes. The surfaces is powder-coated.

VOC

The coating and glue used here reduce VOC emissions in manufacturing processes and finished products. These materials have been tested for formaldehyde emissions in accordance with the ISO12460 standard and confirmed not to exceed the 0.4 mg/l emission level.

PURPOSE OF USE

Indoor

Maruni Wood Industry has established various test standards and designs for comfortable use. However, the use of products beyond the expected scope can lead to cracking and snapping of wood parts. There are several things you should keep in mind in order to properly preserve the product and continue using it for a long time. Therefore, be sure to read the instruction manual beforehand.



OPTION

GLIDE



The leg tips can be equipped with polyethylene gliders, which are sold separately. You can choose between felt and plastic bottom parts.



O1 STOOL Low



O2 STOOL Mid



O3 STOOL High

